



Irrigation Cable

(UL) Approved Sprinkler Systems Cable
and Golf Course Sprinkler Systems Wire



POLYETHYLENE (PE) GOLF COURSE SPRINKLER SYSTEM WIRE
SINGLE CONDUCTOR

(UL) SPRINKLER SYSTEM WIRE
600V - DIRECT BURIAL

PUT-UP: 2,500 FT (2500); 500 FT (500)

e.g. JMC-210013-2500

Single-Conductor Polyethylene Wire for Golf Course Sprinklers

Features

AWG: **10-16AWG**

Type: **Solid Bare Copper**

Insulation: **Colored PVC**

Ratings: **30V 60°C**

Direct Burial

Sunlight Resistant

PART NUMBER	DESCRIPTION	DIAMETER (inches)	LBS/1000 FT (net weight)
JMC-210013	10 AWG SBC - .045 PE - WHITE	0.192	39.6
JMC-210033	10 AWG SBC - .045 PE - YELLOW	0.192	39.6
JMC-212013	12 AWG SBC - .045 PE - WHITE	0.171	26.7
JMC-212023	12 AWG SBC - .045 PE - BLACK	0.171	26.7
JMC-212033	12 AWG SBC - .045 PE - YELLOW	0.171	26.7
JMC-212043	12 AWG SBC - .045 PE - BLUE	0.171	26.7
JMC-212053	12 AWG SBC - .045 PE - BROWN	0.171	26.7
JMC-212063	12 AWG SBC - .045 PE - RED	0.171	26.7
JMC-214013	14 AWG SBC - .045 PE - WHITE	0.154	18.7
JMC-214023	14 AWG SBC - .045 PE - BLACK	0.154	18.7
JMC-214033	14 AWG SBC - .045 PE - YELLOW	0.154	18.7
JMC-214043	14 AWG SBC - .045 PE - BLUE	0.154	18.7
JMC-214053	14 AWG SBC - .045 PE - BROWN	0.154	18.7
JMC-214063	14 AWG SBC - .045 PE - RED	0.154	18.7
JMC-214073	14 AWG SBC - .045 PE - GREEN	0.154	18.7
JMC-214083	14 AWG SBC - .045 PE - ORANGE	0.154	18.7
JMC-214103	14 AWG SBC - .045 PE - PINK	0.154	18.7
JMC-214113	14 AWG SBC - .045 PE - GRAY	0.154	18.7
JMC-214123	14 AWG SBC - .045 PE - TAN	0.154	18.7
JMC-214133	14 AWG SBC - .045 PE - VIOLET	0.154	18.7
JMC-214143	14 AWG SBC - .045 PE - BLACK/WHITE	0.154	18.7
JMC-214153	14 AWG SBC - .045 PE - YELLOW/RED	0.154	18.7
JMC-216013	16 AWG SBC - .045 PE - WHITE	0.141	13.2
JMC-216033	16 AWG SBC - .045 PE - YELLOW	0.141	13.2
JMC-216063	16 AWG SBC - .045 PE - RED	0.141	13.2



SPRINKLER SYSTEM WIRE MULTI-CONDUCTOR CABLES

(UL) SPRINKLER SYSTEM WIRE
30V - DIRECT BURIAL

PUT-UP: 1,000 FT (1000); 500 FT (500)

Black PE Jacket

e.g. JMC-202184-1000

Sprinkler Systems Cables for Underground Sprinkler Systems

Features

AWG: **18AWG**

Type: **Solid Bare Copper**

Insulation: **PVC Color Coded**

Jacket: **Black Polyethylene**

Nylon Ripcord

Ratings: **30V 60°C**

Direct Burial

PART NUMBER	DESCRIPTION	DIAMETER (inches)	LBS/1000 FT (net weight)
JM-202184	2C 18 AWG SBC - .015 PVC/.025 PE	0.190	18.2
JM-203184	3C 18 AWG SBC - .015 PVC/.025 PE	0.205	25.2
JM-204184	4C 18 AWG SBC - .015 PVC/.025 PE	0.222	32.3
JM-205184	5C 18 AWG SBC - .015 PVC/.025 PE	0.242	39.5
JM-206184	6C 18 AWG SBC - .015 PVC/.025 PE	0.264	46.8
JM-207184	7C 18 AWG SBC - .015 PVC/.025 PE	0.264	53.3
JM-208184	8C 18 AWG SBC - .015 PVC/.025 PE	0.285	60.6
JM-209184	9C 18 AWG SBC - .015 PVC/.025 PE	0.307	67.9
JM-210184	10C 18 AWG SBC - .015 PVC/.025 PE	0.334	75.3
JM-212184	12C 18 AWG SBC - .015 PVC/.025 PE	0.345	88.9
JM-213184	13C 18 AWG SBC - .015 PVC/.025 PE	0.351	96.0
JM-219184	19C 18 AWG SBC - .015 PVC/.025 PE	0.403	136.9
JM-225184	25C 18 AWG SBC - .015 PVC/.025 PE	0.474	178.8