

IMSA TRAFFIC SIGNAL CABLE

19-1 SOLID

IMSA 19-1, MULTI-CONDUCTOR

PUT-UPS: 1000 FT (1000); 500 FT (500)

Unshielded, 600V

e.g.JM50906-1000

PE Insulation / Black PVC Jacket

Color Coding per IMSA Specification

Part Number	No. of Conductors	AWG / Solid	Insulation/Jacket Thickness	Diameter (Inches)	LBS/1000 FT (Net Weight)
JM50906	2	14 SBC	.025 / .045	0.329	58
JM43671	3	14 SBC	.025 / .045	0.346	75
JM51379	4	14 SBC	.025 / .045	0.377	93
JM43672	5	14 SBC	.025 / .045	0.409	112
JM43663	7	14 SBC	.025 / .045	0.445	146
JM43725	9	14 SBC	.025 / .060	0.549	200
JM53986	10	14 SBC	.025 / .060	0.593	221
JM43726	12	14 SBC	.025 / .060	0.608	255
JM51380	15	14 SBC	.025 / .060	0.672	307
JM43728	16	14 SBC	.025 / .060	0.672	325
JM53987	19	14 SBC	.025 / .060	0.710	376
JM51475	20	14 SBC	.025 / .060	0.742	397
JM51645	21	14 SBC	.025 / .060	0.742	412
JM51646	25	14 SBC	.025 / .080	0.868	518
JM53988	2	12 SBC	.030 / .045	0.383	80
JM53989	3	12 SBC	.030 / .045	0.405	106
JM53990	4	12 SBC	.030 / .045	0.441	133
JM53991	5	12 SBC	.030 / .045	0.482	161
JM53992	7	12 SBC	.030 / .060	0.555	229
JM53993	9	12 SBC	.030 / .060	0.644	288
JM53994	10	12 SBC	.030 / .060	0.698	320
JM53995	12	12 SBC	.030 / .060	0.721	371
JM53996	16	12 SBC	.030 / .060	0.798	478
JM53997	19	12 SBC	.030 / .080	0.881	589
JM53998	21	12 SBC	.030 / .080	0.925	645
JM53999	25	12 SBC	.030 / .080	1.024	759
JM51305	2	10 SBC	.031 / .045	0.425	109