

Audio and Broadcast Cables

- Sound Systems
- Digital/Analog Video
- Microphone
- Broadcast
- Snake Cable



NEC

Communication and Control Cables

- CM, CMH, CMP, CMR, CMX
- AWM Control Styles for Industrial Applications
- Computer / Data Transmission
- CAD / CAM
- Low Capacitance
- Temperature Control
- Security & Alarm



UL, CSA, USL, CNL, AWM, CM, CMR, CMP, CMX, MP, MPR, CL2, CL2R, CL2P, CL2X, CL3, CL3R, CL3P, CL3X, PLTC, VNTC, TC, DP-1, DP-2, ITC, ST, STO, STOW, SJT, SJTO, SJTOW, SE, SEO, SEOW, SJE, SJEO, SJEOW, SVT, SVTO, VW1, PCC, FT1, FT2, FT4, CMG, IEEE, NEC, 20/10, 30/15, FPL, FPLP, FPLR, NPLF, ZIP

Control and Instrumentation Cables

- Utility 20/10, 30/15
- PLTC & TC PVC & PVC/Nylon
- TC PVC/TPE
- Marine Shipboard IEEE-45
- IMSA
- Bus Drop



Flexible Control Cable, Cords, and Factory Automation

- Continuous Flex UL MTW / AWM / Tray Cables
- High Flex Robotic Cables
- Flat Festoon AWM
- Pendant and Reel
- Crane, Hoist and Conveyor Systems
- Arctic Grade -40°C to +125°C
- Flexible Cords
ST, STO, STOW, SE, SEO, SEOW,
SJT, SJTO, SVT, SVTO, SJE, SJEO, SJEOW



Special Application Cables

- Composite Cable (Custom Designs, Unique Cables)
- Aerial Figure 8
- Multiple-Component Power, Control, Signal Composite
Up to 90 or More, Conductors or Components
- Tensile Load Bearing Members
- Tubing Components for Pneumatic Applications
- Bonded Ribbon Cable AWM



Production Capabilities

Conductors: 32AWG to 500MCM
Insulation: PVC / Nylon / PE / PP / TPR / TPE / PUR
Cabling: Twining, Bunching / Contra-Helical / Planetary
Configurations: Round / Flat / Figure 8
Shielding: Foil / Braids / Spiral Serve / Tapes
Jacket: Up to 2.5" OD - PVC / PE / TPE / TPR / PUR



**All Cables Manufactured
to Meet or Exceed
Product Specifications**

**Low Minimum Orders
4 to 6 Week Deliveries**

